

## **Hardware Comparison Chart**

* • * ·				
Standard Option Not Available		**************************************		
	TA715	TA777/A	TA785	Hand Punch
Employee Capacity	Unlimited	Unlimited	Unlimited	Up to 32,000
Punch Capacity	3000	10000	10000	5000
Biometric Capacity		External	9000	Up to 32,000
Function Keys	8 2 x 16 LCD	8	8	Up to 8
Display		2 x 16 LCD Alphanumeric with	2 x 16 LCD Alphanumeric with separate	2 x 16 LCD Numeric with separate
Keypad/ Input	Alphanumeric	separate function keys	function keys	function Keys
Construction	Plastic	Metal	Plastic	Plastic
Clock battery				
Operational battery	<u> </u>	<u> </u>	<u> </u>	
RS-232 Serial				
RS-485 LAN		<u> </u>		
Modem (14.4) Ethernet 10/100				
Power Over Ethernet	*			*
	×			*
Vireless (802.11b)				
			<u> </u>	
Pin Entry	<b>②</b>	<b>©</b>		<b>©</b>
Magnetic Stripe	<b>⊗</b>	<b>⊗</b>	<b>S</b>	
Bar Code	<b>②</b>	<b>②</b>	<b>S</b>	<u> </u>
Proximity	$\bigcirc$	$\bigcirc$	<b>②</b>	<b>Ø</b>
Biometric	×	External Fingerprint	Fingerprint	Hand Geometry
Data Input Validation	<b>②</b>	External Fingerprint	ringerprint	Hand Geometry
ockout Scheduling	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>	<b>©</b>
imployee Messaging	<b>©</b>	<b>⊗</b>	<b>Ø</b>	<u> </u>
Display Schedule	<b>Ø</b>	<b>S</b>	<u> </u>	<b>O</b>
			~	
Display Hours	<b>©</b>	<b>©</b>	<b>②</b>	<b>②</b>
Display Benefits	<b>©</b>	<b>S</b>	<b>(a)</b>	<b>⊘</b>
Access Controller	<b>⊗</b>	<b>⊗</b>	<b>⊗</b>	<b>⊗</b>
Bell Control	<b>②</b>	<b>②</b>	<b>⊘</b>	<b>⊗</b>
External Reader	×	2 readers	2 readers	<b>②</b>
Bell/Access Relay	igotimes	2 relays	2 relays	igotimes
Connect Sensors	×	2 sensors	2 sensors	×
On-line Operation				×